

# **Quick Start Guide**









## STEP 1: Download and Install the App

Search "CamHipro" on App Store/Google Play, or scan the QR code below to

download and install it on your phone/tablet.



IOS

Scan the QR code to download or Search

"CamHipro" from Apple Store





android

Scan the QR code to download or Search

"CamHipro" from Google Play



STEP 2: Power Adaptor ON + RJ45 to router

Power Adaptor is ON and network cable RJ45 is plug with router

Note: The camera is plug with same router SSID with mobile phone



## STEP 4: Add device ---> Device in use



## STEP 5: Search nearby devices ----> Add to

09:22		,,,   중 ■)	
<b>〈</b> Back	Back Add device		
FILL IN YOUR DE	VICE INFORMATION		
UID:	SSAA-200490-FACDB		
username:	admin		
password:	admin		
GET UID QUICKL	Y		
Scan QR of Scan the de	code evice QR code to get the UID	> number	
Q Search nearby devices > Find the UID number in the same LAN			
	Add to		

## STEP 6: Name setting ----> Confirm

09:22			<b> 🕈 </b>
🕻 Back	Name	setting	$\times$
THE DEVICE H A NAME	AS BEEN ADD	ED SUCCESSF	ULLY! GIVE IT
name:	С	Camera	
quick selecti	on:		
Living room	Bedroom	Doorway	Baby room
Store	Corridor	Hall	Office
	con	firm	
confirm			

## STEP 7: Wireless setting---->Get wireless network around the device --->

## Apply

## Note: SSID MUST be the same as mobile phone with router

09:26 .I 🗢	,
Camera (SSAA-200490-FACDB)	Ŝ
basic settings	
< wireless setting	>
Change Password	>
Alarm Settings	
Alarm management and notification	>
Audio and video management	
<b>Q</b> Video Setting	>
Audio Setting	>
SD card recording and capacity	
SD card plan recording	>
SD Card Setting	>
System settings	
O Time Setting	>

09:27	all S	<b>?</b>
<b>〈</b> Back	wireless setting	
Current Wi-F	ï	
Unknown		>
Get the w	ireless network around the de	vice
TP-LINK_3 singal:100%	68E WPA2_AES	>
ChinaNet-r singal:90%	mYR7 WPA2_TKIP	>
TP-LINK_3 singal:90%	629 WPA2_AES	>
TPGuest_3 singal:86%	629 WPA2_AES	>
ChinaNet-I singal:42%	MjGL WPA2_AES	>
CMCC-SyS singal:38%	Sp WPA2_ТКІР	>
Topway_54 singal:30%	9707 WPA2_AES	>
ChinaNet- singal:22%	5puG WPA2_AES	>

Quick Start Guide / C	Quide de Démarrage Rapide / Guía d	e inicio rápido / Sch	nellstart Anleitur	ng / Guida Rapida
09:27		'II & 🔳		
<b>〈</b> Back	wireless setting			
Wireless name:	TP-LINK_3629			
Password	Password			
	Apply			

## STEP 8: UID is online



English / Français / Español / Deutsch / Italiano

## Forget Password or Factory Default Reset

## AP mode add with camera (Not Wire Plug mode)

## WLAN ---> ON ---> Click "IPCAM-200490" ---> Password "01234567"

09:22		<b>, i ii 🗢 </b>
Settings	WLAN	
WLAN		
✓ IPCAM-2004	90	🔒 🗢 🚺
MY NETWORKS		
TP-LINK_362	29	🛾 🗢 i
OTHER NETWORKS		
ChinaNet-Mj	GL	হ i
ChinaNet-m	′R7	🔒 🗢 і
CMCC-GEas		a 🗢 (i)
CMCC-SySp		🔒 ᅙ 🚺
Topway_5497	707	a 🗢 i
TP-LINK_368	BE	a 🗢 (i)
TPGuest_362	29	🔒 🗢 🚺
TPGuest_ED4	4F	হ i
Other		_

## If more details, please scan the QR code or contact us:

#### tech@vitorcam.com

## Official webpage: www.vitorcam.com

